



	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
COM	COM	1e	1d	1c	DP1	2e	2d	2c	DP2	-	3e	3d	3c	DP3	4e	4d	4c	DP4	5e	5d	5c	DP5	6e	6d	6c	DP6	7e	7d	7c	DP7	8e	8d	8c	8b
	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68
COM	8a	8f	8g	7b	7a	7f	7g	COL3	6b	6a	6f	6g	5b	5a	5f	5g	COL2	4b	4a	4f	4g	3b	3a	3f	3g	COL1	2b	2a	2f	2g	1b	1a	1f	1g

- NOTE:
1. TN TYPE
 2. DRIVING METHOD: STATIC
 3. OPERATING VOLTAGE: 5.0V
 4. OPERATING TEMP: $-0 \sim +50^\circ\text{C}$
 5. STORAGE TEMP: $-10 \sim +60^\circ\text{C}$
 6. VIEWING DIRECTION: 6:00
 7. POLARIZER MODE: REFLECTIVE POSITIVE
 8. CONNECTION: PIN

DWN	Bauing	UNIT	mm	CUST. MODEL	
CKD		SCALE		MODEL	ASI-928
APPD				DATE	DEC-18-2018

1	INITIAL REVISION	DEC-18-2018	ALL SHORE INDUSTRIES, INC	NAME	
REV.	MODIFY CONTENT	DATE		PAGE	1/1